

-- Standard Features --

-- Custom Options --



S Series

SVL97-3HFCC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Final Tier 4 Certified Kubota
Diesel Engine
Electronic Travel Torque
Management System
Vertical Lift Path Loader Frame
Standard Front Quick Coupler,
Float Standard

Hydraulic Quick Coupler Option
Loader Arm Self-Leveling

Loader Boom Lock

Open ROPS/FOPS

Optional enclosed and

pressurized cab with A/C

High Back, Adjustable, Vinyl,

Suspension Seat

Heated, Air Suspension Seat

Standard on Cab Models

2" Retractable Seat Belt And 2-

Piece Seat Bar

12V Electric Outlet

23.1 gpm Auxiliary Hydraulics

Standard, 41.2 gpm Option

Case Drain Line

Rigid Mounted Undercarriage, 5

Lower Track Rollers

High Grip Rubber Tracks, 17.7"

Standard

Two Speed Travel System

Automatic Wet Disk Parking

Brake

Kubota 4 Hydraulic Pump Load

Sensing System

2 Variable Displacement

Pumps

KubotaNOW Telematics

Standard

Lockable DEF Cap Guard

Hydraulic Joystick Controls

ISO Operating Pattern

Dial Knob and Foot Throttle

Controls

Decelerator Pedal

Stall Guard Engine Controls

Automatic Glow Plugs

7" Multifunction Touch Screen

Integrated Rear Camera

Keyless Start

Key Switch Stop System

Self Bleed Fuel System

2 Front and 2 Rear Working

Lights

Hour Meter, Engine Temperatur,

DEF, and Fuel Gauges and

Warning Lights

Horn and Backup Alarm

Lockable Fuel Cap

BASIC UNITS

SVL97-3HFCC, 17.7" Rubber
Tracks,
Open ROPS/FOPS Cab w/ Cold-
weather CCV Package,
Hydraulic Quick Coupler, Flow
Auxiliary Hydraulics, KSR

OPERATIONAL

DIMENSIONS

Operating Weight* 17.7" Rubber
Tracks, Open ROPS/FOPS Cab,
Mechanical Quick Coupler
11,676 lbs.

Rated Operating Capacity (ROC)
@ 35%

of Tipping Load complies with ISO
14397-1

and SAE J 818) 3,511 lbs.
Rated Operating Capacity (ROC)

@ 50%

of Tipping Load 4,850 lbs.
Tipping Load 9,700 lbs.

Auxiliary Hydraulics Flow 23.1/
41.2 gpm

Travel Speed (Low / High) 5.5 /
8.4 mph

Reach @ Maximum Height 40.7"

Height to Hinge Pin 128.6"

Ground Pressure 4.5 psi.

* Includes operator's weight, 175
lbs.

ENGINE

V3800-Tier 4 Kubota Final Tier 4
Diesel Engine

4 Cylinder, 4 Cycle, Turbo Charged
96.4 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 83.1"

Width (without attachment) 77.2"

Length (without attachment) 123.7"

Length of Track on Ground 65.6"

SVL97-3HFCC Base Price: \$105,522.00

Selected Kubota Attachments

(1) SPECIAL APPL DOOR KIT CLOSED CAB \$4,048.00
S6861-SPECIAL APPL DOOR KIT CLOSED CAB

(1) HYDRAULIC QUICK COUPLER GUARD \$288.00
S6974-HYDRAULIC QUICK COUPLER GUARD

(1) AUX COUPLER GUARD \$504.00
S6973-AUX COUPLER GUARD

Selected Land Pride Attachments

(1) CB35 Series Combination Bucket, 80" \$8,631.00
Width15.75-22.33 cu.ft. Heaped

AP-CB3580-01-20-10-CB35 Series Combination Bucket, 80"
Width15.75-22.33 cu.ft. Heaped

(1) 5500 lb. 56 Series Pallet Fork, 48" Width5,500 \$1,820.00
lb. Capacity

AP-PFL5648-99-5500 lb. 56 Series Pallet Fork, 48" Width5,500
lb. Capacity

Total Kubota Attachments: \$4,840.00

Total Land Pride Attachments: \$10,451.00

Total Attachments: \$15,291.00

Configured Price: \$120,813.00

Sourcewell Discounts:

Kubota Items: (\$26,486.88)

Land Pride Items: (\$2,612.75)

Total Discount: (\$29,099.63)

SUBTOTAL: \$91,713.37

Kubota Item Fees:

Dealer Assembly: \$0.00

Freight Cost: \$718.75

PDI: \$400.00

36" SMOOTH BUCKET FOR KX057 \$2,250.00

Total Unit Price: \$95,082.12

Quantity Ordered: 1

Final Sales Price: \$95,082.12

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.